

## CARATTERISTICHE HARDWARE PianetaFibra Box 6

Interfaccia	4 10/100/1000Mbps RJ45 LAN Ports, 1 10/100/1000Mbps RJ45 WAN Port, 1VDSL2 Port, 2 FXS Ports, 1 USB 2.0 Ports
Tasto	Power On/Off Button, Reset Button, WPS On/Off Button, Wireless On/Off Button
Alimentatore esterno	12V/2.0A
Standard IEEE	IEEE 802.3, IEEE 802.3u, 802.3ab
Standard VDSL2	ITU G.993.2, Up to 35b profile ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)
Standard	Full-rate ANSI T1.413 Issue 2,

ADS L	ITU-T G.992.1(G.DMT),  ITU-T G.992.2(G.Lite),  ITU-T G.994.1 (G.hs),  ITU-T G.995.1
Standard ADS L2	ITU-T G.992.3 (G.DMT.bis)  ITU-T G.992.4 (G.lite.bis)
Standard ADS L2+	ITU-T G.992.5
Dimensioni (L x P x A )	8.4 × 5.7 × 3.2 in. (214.0 × 144.5 × 80.0 mm)

## CARATTERISTICHE WIRELESS

Standard wireless	IEEE 802.11 ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
----------------------	--

Frequenza	2.4GHz and 5GHz(not Supports DFS)
Signal rate	1201Mbps at 5GHz, 300Mbps at 2.4GHz
Potenza di trasmissione	<20dBm (2.4GHz), <23dBm (5GHz)
Funzionalità wireless	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Sicurezza wireless	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions
Schedulazione wireless	Support 2.4GHz and 5GHz Wireless Schedule

## CARATTERISTICHE SOFTWARE

QoS (Quality of Service)	ATM QoS, Bandwidth Control
Sicurezza	NAT Firewall, SPI Firewall, Access Control, Service Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding
Gestione	Web Based Configuration (HTTP), Remote management, Command Line Interface, SSL for TR-069, SNMP v1/2c, Diagnostic Tools, Web Based Firmware Upgrade
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP

Dyna mic DNS	DynDns, NO-IP
VPN	OpenVPN, PPTP VPN, IPsec VPN
Proto colli	Support IPv4 and IPv6
Carat teristi che ATM	ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MERIPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
Funzi onalit à avan zate	Auto Gateway, Parental Controls, Network Address Translation(NAT), Port Mapping (Grouping), Static Routing, RIP v1/v2 (optional), DNS Relay, DDNS, IGMP V1/V2/V3
Cond ivisio ne USB	Support Samba (Storage) / FTP Server / Media Server, 3G/4G Modem

Rete ospiti	2.4GHz and 5GHz multi SSID
VPN IPsec	Support up to 16 IPsec VPN tunnels

## ALTRO

Certificazione	CE
Requisiti di sistema	<p>Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux</p> <p>Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser</p>
Ambiente	<p>Operating Temperature: 0°C~40°C (32°F ~104°F)</p> <p>Storage Temperature: -40°C~70°C (-40°F ~158°F)</p> <p>Operating Humidity: 10%~90% non-condensing</p>

	Storage Humidity: 5%~90% non-condensing
--	--